




STARLINK

KVH is a Starlink Authorized Tier 1 Reseller

Four Starlink Antenna Options

Authorized for Use In Motion



Starlink products are not shown to scale.

	Starlink Performance Kit (Gen 3)	Starlink Performance Kit (Gen 2)	Starlink Standard	Starlink Mini
KVH Part Number	72-1113 part number varies by Mount and Router choices (four Mounts with or without Router)	72-1048 includes Gen 3 Wi-Fi Router; or 72-1048-OEM (no Router)	72-1081 includes Gen 3 Wi-Fi Router	72-1102 with integrated Wi-Fi, kickstand and pipe adapter
Dimensions	609 x 396 x 40 mm (24 x 15.6 x 1.6 in)	575 x 511 x 41 mm (22.6 x 20.1 x 1.6 in)	594 x 383 x 40 mm (23.4 x 15.1 x 1.6 in)	259 x 298 x 37 mm (10.2 x 11.75 x 1.45 in)
Weight	5.2 kg (11.5 lbs)	5.9 kg (13 lbs)	2.9 kg (6.4 lbs)	1.2 kg (2.6 lbs)
Avg Power Draw	70 W	110 W	62 W	25-40W
Power Specifications	100-240VAC, 12V-56VDC	100-240V AC	100-240V AC	DC Power Cable
Peak Throughput	470/48 Mbps (down/up)	450/47 Mbps (down/up)	470/48 Mbps (down/up)	100/10 Mbps (down/up)
Field of View	140°	140°	110°	110°
Router Compatibility	Third party compatible	Third party compatible	Requires Advanced Power Supply to support third party routers	Third party compatible
Power Supply Environmental Rating	IP68 (with cables installed or plugged)	IP66	IP66 Type 4	IP67 Type 4 with DC Power Cable and Starlink Plug/Cable installed
Dish Environmental Rating	IP69K (with cables installed) IP68 (no cables installed)	IP56 (with cables installed) Not Rated (no cables installed)	IP67 Type 4 (with cables installed) Not Rated (no cables installed)	IP67 Type 4
Snow Melt Capability	Up to 85mm / hour (3.5 in / hour)	Up to 85mm / hour (3.5 in / hour)	Up to 40 mm / hour (1.5 in / hour)	Up to 25mm / hour (1 in / hour)
Operating Temperature	-40°C to 60°C (-40°F to 140°F)	-30°C to 50°C (-22°F to 122°F)	-30°C to 50°C (-22°F to 122°F)	-30°C to 50°C (-22°F to 122°F)
Wind Speed Rating	Survivable: 280 kph+ (174 mph+)	Survivable: 280 kph+ (174 mph+)	Survivable: 177 kph+ (110 mph+)	Compact in size, portable, and recommended for basic internet applications
Field of View	140°	140°	110°	140°
Available Cable Lengths *included in kit	5m, 25m*, 50m, 50m LSZH	2m, 25m*, 8m	15m*, 50m	Low power consumption No RF shielding
Cable Connectors	Starlink Performance to Starlink RJ45 Able to field terminate	High Performance Starlink Connector to Starlink Gen2 Router Connector	Starlink RJ45 to Starlink RJ45	Starlink RJ45 to Starlink RJ45
Mounting Options	Wedge Mount Flat Mount Pipe Adapter Wall Mount	Wedge Mount Flat Mount Pipe Adapter	Wall Mount Pivot Mount Pipe Adapter Mount Ridgeline Mount Mobility Mount X-Frame Base Pipe Adapter Mount Roof Rack Mount Base	Wall Mount Pivot Mount Mobility Mount Roof Rack Mount Mini Pipe Adapter and Flat Mount
Warranty Length	3 years	2 years	1 year (except mandatory 24 months in UK/EU)	



Visit kvh.com/offices for regional headquarters and sales locations and contact details.

